

STT	Quy cách	PR	Loại	Chỉ số		Áp lực bơm		Tải trọng tối đa		Tốc độ tối đa	Bề rộng	Đường kính	Độ sâu gai	Trọng lượng	Rộng vành
			TT/TL	Tải	Tốc độ	kgf/cm2	PSI	Đơn/kg	Đôi/kg	kg/h	mm	mm	Mm	kg	inch
1	4.50-12	12	TT	86/84	J	5.62	80	530	500	100	125	550	8	5.9	3
2	5.00-12	8	TT	83/81	J	4.07	58	487	462	100	137	586	10	6.9	3.5
3	5.00-12	12	TT	92/90	J	5.62	80	630	600	100	137	586	10.5	8	3.5
4	5.00-12 BG	12	TT	91/90	J	5.5	78	615	600	100	138	583	10.5	7.6	3.5
5	5.00-12 HD	14	TT	100/99	J	6.39	91	800	775	100	137	586	10.5	8.6	3.5
6	5.00-13	12	TT	100/98	J	5.83	83	800	750	100	156	627	11.5	9.6	3.5
7	5.50-13	12	TT	100/98	J	5.83	83	800	750	100	156	627	11.5	9.6	4
8	5.50-13 HD	12	TT	102/100	K	6.6/6.1	94/87	850	800	110	156	630	11.5	9.4	4
9	5.50-13 HD	14	TT	103/100	J	6.6	94	875	800	100	156	627	11.5	10	4
10	5.50-13 HD	14	TT	103/100	K	6.6	94	875	800	110	156	627	11.5	10	4
11	5.50-13 OVERSIZE	14	TT	106/104	J	6.11	87	950	900	100	166	600	13	13	4.5
12	6.00-13	12	TT	106/104	J	6.11/5.83	87/83	950	900	100	166	660	13	12.2	4.5
13	5.50-14	12	TT	107/105	J	5.83	83	975	925	100	175	684	13	12.2	4
14	5.50-14	12	TT	107/105	K	5.83	83	975	925	110	175	684	13	12.2	4
15	6.00-14	12	TT	107/104	J	5.83	83	975	900	100	175	683	13	12.2	4.5
16	6.00-14	14	TT	111/108	J	6.6	94	1090	1000	100	175	683	13	13	4.5
17	6.00-14	14	TT	111/108	K	6.6	94	1090	1000	110	175	683	13	13	4.5
18	6.50-14	12	TT	102/100	J	4.35	62	850	800	100	182	693	13	12	4.5
19	6.50-14	14	TT	112/110	J	6.6	94	1120	1060	100	182	693	13	12	4.5
20	6.00-15	10	TT	103/101	J	5.13	73	875	825	100	167	709	13	13.6	4.5
21	6.00-15	14	TT	113/111	K	6.12	87	1150	1090	110	171	704	12.3	13.75	4.5
22	7.00-15	12	TT	114/112	J	5.83	83	1180	1120	100	199	758	15	17.2	5.5
23	7.00-15	14	TT	117/115	J	6.6	94	1285	1215	100	199	758	15	18	5.5
24	7.00-15	14	TT	117/115	K	6.6	94	1285	1215	110	199	758	15	18	5.5
25	7.50-15	14	TT	121/119	J	6.6	94	1450	1360	100	224	788	16	18.5	6
26	6.50-16	12	TT	111/109	J	5.83	83	1090	1030	100	182	750	14	14.4	4.5
27	6.50-16	14	TT	114/112	J	6.6	94	1180	1120	100	182	750	14	14.4	4.5
28	6.50-16	14	TT	114/112	K	6.5	92	1180	1120	110	181	750	14	14.9	4.5
29	7.00-16	14	TT	118/116	J	6.11	87	1320	1250	100	201	781	15	16.8	5.5
30	7.00-16	16	TT	121/119	J	6.6	94	1450	1360	100	201	781	15	25.5	5.5
31	7.00-16 HD	16	TT	124/122	J	6.6	94	1600	1500	100	201	781	18	25.5	6
32	7.00-16 2VT	16	TT	121/119	J	6.6	94	1450	1360	100	201	781	14.5	25.5	5.5
33	7.00-16 HD	16	TT	123/121	K	7.38/7.17	105/102	1550	1450	100	201	781	15	25.5	5.5
34	7.50-16	10	TT	118/116	L	5.35	76.1	1320	1250	120	212	819	18.3	20.3	6
35	7.00-16 OVERSIZE	16	TT	109	J	7.38/7.17	105/102	1550	1450	100	214	808	15	25.2	6
36	7.50-16	16	TT	124/122	J	7.66	109	1580	1510	100	214	808	18	25.2	6
37	7.50-16 HD	16	TT	124/122	J	7.66	109	1600	1500	110	199	758	18	25.2	6
38	7.50-16 HD	18	TT	125/124	J	8.15	116	1950	1800	100	214	808	18	26	6
39	7.50-16	18	TT	125/124	J	8.15	116	1950	1800	100	214	808	18	26	6
40	7.50-16	20	TT	123/120	J	8.15	116	2080	1980	100	214	808	18	25	6
41	8.25-16	18	TT	131/127	J,K,L	8.15	116	1950	1750	120	230	862	20	30	6.5
42	8.25-16	20	TT	133/128	J,K	8.15	116	2060	1800	110	230	862	20	30	6.5
43	8.25-16 HD	20	TT	123/120	K	8.15	116	2120	2000	110	230	862	20	30	6.5
44	8.25-16	20	TT	137/135	G	8.92	127	2300	2180	90	231	868	20	33	6.5