

Quy cách Size	Số lớp vải chuẩn	Vành chuẩn	Áp suất bơm tối đa				Tải trọng tối đa				Đường kính (mm) Overall Diamete r (mm)	Chiều rộng mặt cắt Section Width (mm)
	Ply Raitng	Measuring Rim	Max air				Max load					
			PSI		KPA		LBS		KGS			
			ĐƠN (S) Single	KÉP (D) Double	ĐƠN (S) Single	KÉP (D) Double	ĐƠN (S) Single	KÉP (D) Double	ĐƠN (S) Single	KÉP (D) Double		
5.00-10	12	3.50BX10	85	80	590	550	1074	1019	487	462	517	137
5.00-12	12	3.50BX12	85	85	590	590	1230	1170	560	530	568	135
5.00-12	14	3.50BX12	85	85	595	595	1720	1675	780	760	598	150
(155/80-13) 5.00-	14	4.00BX13	85	85	590	590	2090	1980	950	900	596	157
5.00-13	14	4.00BX13	85	85	600	600	1870	1760	850	800	596	157
5.50-13	12	4.00BX13	85	85	590	590	1870	1760	850	800	623	157
5.50-13	14	4.50BX13	85	85	590	590	2090	1980	950	900	655	172
6.00-13	14	4.50BX13	75	75	530	530	1741	1620	790	735	669	175
6.00-14	14	4.50JX14	85	85	590	590	2200	2090	1000	950	680	172
6.50-14	14	4.50JX14	85	85	590	590	2200	2090	1000	950	680	172
6.00-15	14	4.50E SDCX15	85	85	590	590	2530	2400	1150	1090	727	175
6.50-15	14	4.50E SDCX15	85	85	590	590	2530	2400	1150	1090	727	175
6.50-16	14	5.00E SDCX16	85	85	590	590	2600	2460	1180	1120	753	180
7.00-15	14	5.50F SDCX15	90	90	620	620	2830	2670	1285	1215	754	199
7.00-16	14	5.50F SDCX16	115	115	810	810	2975	2623	1350	1190	779	199
7.00-16	16	5.50F SDCX16	105	105	720	720	3410	3190	1550	1450	779	199
7.00-16 Newtyre	16	6.00GS SDCX16	110	110	760	760	3850	3520	1750	1600	808	214
7.50-16	16	6.00GS SDCX16	110	110	760	760	3850	3520	1750	1600	808	214
7.50-16	18	6.00GS SDCX16	125	120	860	830	4290	3960	1950	1800	808	214
8.25-16	18	6.50H SDCX16	115	115	790	790	4290	3960	1950	1800	858	236
8.25-16	20	6.50H SDCX16	125	120	860	830	4674	4409	2120	2000	858	236